



LUXOR PAINTS (Pty) LTD
Cnr Griffith & Jet Park Rds, Boksburg
P.O Box 14184, Witfield, 1467
Tel: +27(0)-11-397-6622 Fax: +27(0)-11-397-8670



Name : LUXLINE N/C SATIN BLACK Code : 400-406 Date Issued : 2005/08/19



Flammable



Harmful



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Name : LUXLINE N/C SATIN BLACK Code : 400-406 Date Issued : 2005/08/19
CAS no. : n/a EC no. : n/a
UN No. : 1263 EAC : 127 Hazchem : 3[Y]E Kemler : 30 SAPMA : 2-H-E
In emergency contact : Luxor Tel.: (011) 397 - 6622 Fax: (011) 397 - 8670 Cell: 083 554 1993

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC Classification : F Xn R11,20,36,43,66,67 S02,13,16,24,26,37,43A,46,51

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

TOLUENE >12.5%
[CAS #: 108-88-3] [E.C. #: 601-021-00-3]
EEC Labels : F XN OEL 188mg OEL 50ppm STOEL 560mg STOEL 150ppm RL+ S

N-BUTANOL >5%
[CAS #: 71-36-3] [E.C. #: 603-004-00-6]
EEC Labels : XN OEL 150mg OEL 50ppm STOEL 150mg STOEL 50ppm RL S

ROSIN >1%
[CAS #: 8050-09-7] [E.C. #: 650-015-00-7]
EEC Labels : XI OEL 10TDppm SUG

XYLENE <12.5%
[CAS #: 1330-20-7] [E.C. #: 601-022-00-9]
EEC Labels : XN OEL 435mg OEL 100ppm STOEL 650.mg STOEL 150.ppm RL+ S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating : 2-MODERATE - Temporary or minor injury possible even if treatment given
Inhalation : HARMFUL. Excessive exposure to this material must be avoided.
Skin : HARMFUL BY CONTACT. Potential sensitiser.
Eyes : Irritating - may cause damage if not given prompt attention.
Ingestion : Harmful if sw allowed. Can affect CNS. Systemic poison.
No carcinogenic, mutagenic or genetic effects established
Medium to long term environmental effects. Contain, collect & remove.
Skin Sensitiser

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. In case of discomfort seek medical attention.
Skin : Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes : Rinse well with water and seek medical advice if discomfort persists.
Ingestion : Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Highly flammable with toxic fumes.
Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!
Foam. Dry powder. Fog to cool and control. Do NOT use water jets.
Cool containers in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Use an inert - NOT saw dust. Keep out of drains & sewers.

SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.
No open flames. No smoking. No sparks.
Keep containers cool. Avoid free fall of liquid - use earthing.
Subject to local bylaws

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAPMA Rating : 2-H-E PPE : Respirator and Eye protection

Inhalation : In case of insufficient ventilation, use suitable respiratory protection.

Skin : Avoid direct contact. Use barrier cream and impervious gloves.

Eyes : Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves.

Ingestion : Observe the rules of hygiene. Wash before eating, drinking or smoking.

OEL Type : Mixture- Mixture - See Section 2 Skin annotation

Skin Sensitiser



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical class : PAINT Description : Viscous liquid Smell : Pungent

Visc. : 100KU SG : 1.04 pH : t.b.e. NV : 33%

Boil. pt (°C) : >35

FlashPoint (°C) : <23 (derived)

--

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions

Prone to ignite by static

Unstable to heat &/or slight reaction with water

SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established

LD50 Oral: >500 mg (derived)

SECTION 12. ECOLOGICAL INFORMATION

Medium to long term environmental effects. Contain, collect & remove.

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

SECTION 14. TRANSPORT INFORMATION

UN No. : 1263 : PAINT PRODUCT

Packing group : II IMO Class : 3.2

EAC : 127 Hazchem : 3[Y]E Kemerl : 30



SECTION 15. REGULATORY INFORMATION

EC no. : n/a Contains : TOLUENE, N-BUTANOL, ROSIN

EC Classification : F Xn R11,20,36,43,66,67 S02,13,16,24,26,37,43A,46,51

R11 - Highly Flammable

R20 - Harmful by inhalation

R36 - Irritating to the eyes

R43 - May cause sensitisation by skin contact

R66 - Repeated exposure may cause skin drying or cracking

R67 - Vapours may cause drowsiness and dizziness.

S2 - Keep out of reach of children. (Retail sales items)

S13 - Keep away from food, drink and animal feeding stuffs

S16 - Keep away from sources of ignition - No smoking

S24 - Avoid contact with the skin

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37 - Wear suitable gloves

S43A - In case of fire, use water fog, foam or powder - Do not use water jets!

S46 - If swallowed seek medical advice immediately and show this container or label

S51 - Use only in well ventilated areas



Flammable



Harmful

SECTION 16. OTHER INFORMATION

THIS SUBSTANCE IS A POTENTIAL SENSITISER - ENSURE PRECAUTIONS ARE TAKEN.
IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 2005/08/19 Date of analysis : 2005/08/19)

